

FTM FS-1F



It is used for different kinds of modules and applied to the working area subsystem.

It uses embedded surface frame, easy to install and disassemble, it is with protective door and dusty free; can do OEM for any customers and print request LOGO

With application of fiber SC/LC simplex, duplex and other different environment installed plate or flush plate. All modules can be configured on customer's choice;

All modules are free of welding

Model and configuration

Module NO:	Size:L*W*H	Mounting way	Cable way	Cable way
FTM FS-1F	115*86*23(mm)	Wall mounting (indoor)	Uncutting	1pc SC adapter or 1pc Double LC

1. The telecommunication network ,metropolitan area network, optical fiber communication system
2. Optical testing equipment/instrument
3. CATV optical fiber, optical fiber sensor
4. Optical fiber broadband access network, FTTH Optical fiber
5. Optical fiber distribution frame, frame type and wall type Optical fiber distribution unit

Performance

Item	Technical Data
Application	3.0X2.0 mm drop cable or indoor cable
Fiber diameter	125um(652&657)
Tight cladding diameter	250um&900um
Mode of application	Single mode & duplex mode
Tensile strength	<50N
End-use temperature	-40~+85°C
Adaptor	SC&FC
Insertion loss	≤0.2Db(1310nm&1550nm)
Output	2

DATA SHEET

Specifications may change without notice. Display Product Photos Shown are samples for viewing, not actual products. Colours and styles may vary.